

- High-Power white LED light
- rechargeable
- with docking station



LPL12X1

See better, work better

Cordless professional lighting tool

The rechargeable Philips LED inspection lamp with docking station is the cordless professionnal lighting tool. Its strip LED gives a strong and homogenous beam, that illuminates every area abundantly.

High-Power white LED light

- Light output: 200 lumens
- \bullet Wide beam angle: up to 70°

Hands-free lighting

- · Cordless professional lighting tool
- Versatile clipping and magnet hook

High resistance

- Resistant to chemical & workshop solvents
- Strong impact resistance -IK07
- Water & dust protected -IP65

Slim design for confined spaces

· Eliminates all shadows



Highlights

Light output: 200 lumens



The high power white LED's provide 200 lumens of light output to ensure that you are not left in the dark when trying to spot even the smallest details. The colour of the light is soft natural white with a colour temperature of 6000 K, the best solution for long-time repair jobs because it does not strain the eyes.

Wide beam angle



The wide beam angle of 70° will enable you to focus on specifics part and to deliver the right amount of light you need.

Eliminates all shadows

Eliminates all shadows

Water & dust protected -IP65



The LED inspection lamp is water resistant, and conforms to IP65.

Strong impact resistance -IK07



Strong impact resistance -IK07

Versatile clipping and magnet



With the adjustable & retractable multi-angle hook you will have the possibility to hang this professional lighting tool on every surface. Leaving your both hands free for the job.

Resistant to chemical



Grease and solvent resistant

As well as resisting knocks, the case for our inspection lamp are resistant to water, chemical and workshop solvents.

Cordless professional lighting



Versatile and easy to use, the LED inspection lamp RCH20 is up to any job. Suitable for mechanic work, plumbing jobs, electric maintenance or any other foreseeable job due to its rechargeable battery with high autonomy.

Specifications

Maximum visibility

- Beam angle: 70°
- Color temperature: 6000 K
- Light output: 200 lumens
- Number of LED: 1 strip LED

Versatile

• Hook: 360° retractable hook

Robust

- Impact protection rating (IK): IK07
- Ingress protection ration (IP): IP65
- Operating temperature: -10°C to 40°C

Power

• Battery lifetime: 3 hr

Technical specifications

- Battery run time: up to 3 hours
- · Charging time: 4 hours
- Lamp dimensions (mm): 190 Length * 38 Wide * 63 deep
- Operating line voltage: 100-240V
- Power consumption: 2,4W

Product weight

• without docking station: 210 g

Outer Carton

- Number of consumer packagings: 6
- Outer carton (L x W x H): 26.9 x 16.5 x 12.1 cm
- Gross weight: 1.19 kg
- GTIN: 1 87 27900 38946 0



Issue date 2013-08-30

Version: 3.1.4

12 NC: 9237 956 30101 EAN: 87 27900 38946 3 © 2013 Koninklijke Philips N.V. All Rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. or their respective owners.

www.philips.com